

### PROCESSOR

600 MHz, Arm Cortex-A9 32-bit RISC, 1500 MIPS

### MEMORY

1024 MB (512 MB Flash, 512 MB SDRAM), microSD

### DISPLAY

3.5" (320 × 480) HVGA capacitive touchscreen, Corning® Gorilla® Glass 3 technology

# PRINTER

30 lps, 40 mm paper roll

# OPERATING SYSTEM

V/OS (Linux-based)

### CONNECTIVITY

3G, Bluetooth 4.2 BLE, 5 GHz + 2.4 GHz WiFi

## CARD READERS

Triple track MSR: ISO 7810, 7811, 7813; smart card reader: EMVCo-approved

sized merchants around the globe.

### CONTACTLESS

ISO 14443 Types A and B, ISO 18092-capable, MIFARE, supports major NFC/CTLS schemes

## SCANNER/CAMERA

1D/2D barcode reader, 5 MP AF camera

### KEYPAD

Backlit; optional privacy shield

### AUDIO

Speaker

### SECURITY

PCI PTS 5.X-approved, SRED

# POWER SUPPLY

An Engage portable device that combines payment acceptance, receipt printing, barcode scanning and image capture—to power small to mid-

Battery: 3.7 V/2450 mAh Li-lon
PSU: 100-240 VAC w/ output DC 5 V, 1 amp

### ENVIRONMENTAL

Operating temperature: 0° to 50° C (32° to 122° F)

Storage temperature: -20° to 60° C (-4° to 140° F)

Relative humidity: 5% to 90%, non-condensing

### PHYSICAL

 $172.4 \text{ mm L} \times 75.3 \text{ mm W} \times 54.6 \text{ mm H};$  330 g

### OTHER STANDARD FEATURES

2 SAM slots, geolocation, dual SIM